

Xenon Strobe



Model No. CTO15x



Made of durable polycarbonate plastic. Strobes are used as warning lights and in emergency situations to attract attention. They are easily visible in broad daylight. The lens and body can be unscrewed to allow for replacement of the flash tube. The specific parameters of each model are explained below.



Available in three colors.

Features

- High intensity, visible in direct sunlight.
- Long lamp life (8000 hours)
- Three easy mounting styles
- Provides 360 degree visibility
- Polycarbonate lens
- UL Listed Type 4X environments, File E319448
- Rated IP66
- CE approved
- Available with red, amber or clear lens
- Replaceable flash tube

Technical Specifications

- Voltage: See model info
- Current: See model info
- Flash Rate: 72 Flashes/Minute
- Flash Tube: Xenon
- Intensity: 150,000 candela
- Standards: UL1638

	CTO15A	CTO15B	CTO15C	CTO15F
Voltage	120VAC	12 to 80VDC	120VAC	120VAC
Current	0.08A	0.25A	0.08A	0.08A
Base	E26 Screw in	1/2" NPT male	1/2" NPT male	1/2" NPT female
Dimensions	2.8"Ø x 6.5"H	2.8"Ø x 6.4"H	2.8"Ø x 6.4"H	2.8"Ø x 6.3"H

